[CLASS XII PHYSICS PRACTICALS]

TERM- 1 Evaluation Scheme) 2021-2022 Examination Marks

Two experiments one from each section	08
Practical Record (Experiment and Activities)	02
Viva on Experiment, and Activities	05
	Total 15

TERM- 2 Evaluation Scheme) 2021-2022 Examination Marks

Two experiments one from each section	08
Practical Record (Experiment and Activities)	02
Viva on Experiment, and Activities	05
	Total 15

Note:- 1. Term-1 Practical's (1 to 7)

- 2. Term-2 Practical's (8 to 14)
- 3. Graph of Experiment No. 1 (Term 1) and 9,10,13,14 (Term-2) are to written on blank pages.
- 4. Observation table of experiment are to be drown on blank pages.
- 5. Leave one page after Term-1 Practical's and then write Term-2 Practical's.
- 6. Start each experiment from a new page.
- 7. Activities file work is also included in the practical syllabus in Term-1 and Term-2. For project work contact the teacher for the topic.
- 8. Practical & Activity File note book should be hand written.

PHYSICS PRACTICAL TERM-1

EXPERIMENT – 1

Aim: To determine resistance per cm of a given wire by plotting a graph of potential difference versus current. **Apparatus:** A metallic conductor (coil or a resistance wire), a battery, one way key, a voltmeter and an ammeter of appropriate range, connecting wires and a piece of sand paper, a scale.

Formulae Used: The resistance (R) of the given wire (resistance coil) is obtained by Ohm's Law $\frac{V}{I} = R$

Where, V : Potential difference between the ends of the given resistance coil. (Conductor) I: Current flowing through it.

If *l* is the length of resistance wire, then resistance per cm of the wire = $\frac{R}{l}$

Observation:

(i) Range:

Range of given voltmeter = 3 vRange of given ammeter = 500 mA



(ii) Least count:

Least count of voltmeter = 0.05v

Least count of ammeter = 10 mA

(iii) Zero error:

Zero error in ammeter, $e_1 = 0$

Zero error in voltmeter, $e_2 = 0$

Ammeter and Voltmeter Readings:

C N	Ammeter Reading I (A)		Voltmeter R	V p	
Sr. 10.	Observed	Value	Observed	Value	$\frac{I}{I} = K$
1	50	500 mA	16	16x0.05=0.8	1.6Ω
2	35	350 mA	11	0.55	1.57 Ω
3	32	320 mA	10	0.50	1.56Ω
4	19	190 mA	6	0.30	1.58Ω
5	10	100 mA	3	0.15	1.5Ω

Mean R = 1.56

Length of resistance wire: 28 cm

Graph between potential difference & current:

Scale: X - axis : 1 cm = 0.1 V of potential difference

Y - axis: 1 cm = 0.1 A of current

The graph comes out to be a straight line.



Result: It is found that the ratio V/I is constant, hence current voltage relationship is established i.e. $V \propto I$ or Ohm's Law is verified.

Unknown resistance per cm of given wire = $5.57 \times 10^{-2} \Omega \text{ cm}^{-1}$

Precautions: Voltmeter and ammeter should be of proper range.

• The connections should be neat, clean & tight.

Source of Error: Rheostat may have high resistance.

The instrument screws may be loose.

EXPERIMENT – 2

Aim: To find resistance of a given wire using Whetstone's bridge (meter bridge) & hence determine the specific resistance of the material.

Apparatus: A meter bridge (slide Wire Bridge), a galvanometer, a resistance box, a laclanche cell, a jockey, a oneway key, a resistance wire, a screw gauge, meter scale, set square, connecting wires and sandpaper.



Formulae Used:

(i) The unknown resistance X is given by:

$$\mathbf{X} = \frac{(100 - l)}{l} \times R \qquad \text{Where}$$

R = known resistance placed in left gap.

X = Unknown resistance in right gap of meter bridge.

l=length of meter bridge wire from zero and upto balance point (in cm)

(ii) Specific resistance (ρ) of the material of given wire is given $\rho = \frac{X\pi D^2}{4L}$

Where,

D: Diameter of given wire

L: Length of given wire.

Observation Table for length (*l*) & unknown resistance, X:

Sr. No.	Resistance from resistance box R (ohm)	Length AB = <i>l</i> cm	Length BC = (100-l) cm	Unknown Resistance $\mathbf{X} = \mathbf{R} \cdot \frac{(100-l)}{l} \Omega$
1	2	41	59	2.87
2	4	60	40	2.66
3	6	69	31	2.69
4	8	76	24	2.52

Table for diameter (D) of the wire:

		Circular Sc	Observed diameter	
Sr. No.	Linear Scale Reading (N) mm	No. of circular scale divisions coinciding (n)	Value n x (L.C.) mm	$D = N + n \times L.C.$ mm
1	0	34	0.34	0.34
2	0	35	0.35	0.35
3	0	36	0.36	0.36
4	0	35	0.35	0.35

Observations:

• Least count of screw gauge: 0.001 cm

Pitch of screw gauge: 0.1 cm

Total no. of divisions on circular scale: 100

Least Count = <u>Pitch</u>

 $\frac{1}{No. of divisions on circular scale}$

 $\therefore LC = 0.001 \, cm$

- Length of given wire, L = 25cm Calculation:
- For unknown resistance, X: Mean X = $\frac{X_1 + X_2 + X_3 + X_4}{4} = 2.68\Omega$

• Mean diameter,
$$D = \frac{D_1 + D_2 + D_3 + D_4}{4} = 0.035 \, cm$$

• Specific Resistance,
$$\rho = X \cdot \frac{\pi D^2}{4L} = 1.03 \times 10^{-4} \Omega \, cm$$

Result: Value of unknown resistance = 2.68Ω

Specific resistance of material of given wire $=1.03 \times 10^{-4} \Omega cm$

Precautions: All plugs in resistance box should be tight. Plug in key, K should be inserted only while taking observations.

Sources of Error: Plugs may not be clean.

Instrument screws maybe loose.

Aim: To verify the laws of combination (series & parallel) of resistances using meter bridge (slide Wire Bridge) **Apparatus:** A meter bridge, laclanche cell, a galvanometer, a resistance box, a jockey, two resistances wires, set square, sand paper and connecting wires.



Observations: Table for length (1) & unknown resistance (r):

Resistant Coil	Obs. No.	Resistance from resistance box, R (ohm)	Length $AB = l (cm)$	Length BC = 100 - <i>l</i> (cm)	Resistance $\mathbf{r} = \frac{100 - l}{l} \cdot R$	Mean Resistant (ohm)
	1	0.5	35	65	0.92	
r ₁ only	2	1.0	43	57	1.32	1.24
	3	1.5	50	50	1.5	
	1	0.5	30	70	1.16	
r ₂ only	2	1.0	38	62	1.63	1.51
	3	1.5	46	54	1.76	
	1	1.3	34	66	2.52	
$\mathbf{r}_1 \propto \mathbf{r}_2 \ln$	2	2.2	45	55	2.68	2.72
series	3	3.5	54	46	2.97	
$r_1 \& r_2$ in	1	2	75	25	0.67	
	2	3	82	18	0.66	0.66
paraner	3	4	86	14	0.65	

Calculations:

(i) In Series: Experimental value of $R_s = 2.72 \ \Omega$

Theoretical value of
$$R_s = r_1 + r_2 = 2.75 \ \Omega$$

(ii) In parallel: Experimental value of $R_P = 0.66 \Omega$

Theoretical value of
$$R_P = \frac{r_1 r_2}{r_1 + r_2} = 0.68\Omega$$

Result: Within limits of experimental error, experimental & theoretical values of R_s are same. Hence the law of resistance in series i.e. $R_s = r_1 + r_2$ is verified. (1) Within limits of experimental error, experimental & theoretical

values of R_P are same. Hence law of resistances in parallel i.e. $R_s = \frac{r_1 r_2}{r_1 + r_2}$ is verified.

Precautions:

- (i) The connections should be neat, clean & tight.
- (ii) Move the jockey gently over the wire & don't rub it.
- (iii) All plugs in resistant box should be tight.

Sources of Error:

- (i) The plugs may not be clean.
- (ii) The instrument screws maybe loose.

EXPERIMENT-4

Aim: To compare the E.M.F.'s of two given primary cells using a potentiometer.

Apparatus: A potentiometer, a laclanche cell, a Daniel cell, an ammeter, a voltmeter (0-5v), a galvanometer, a battery (or battery eliminator), a rheostat of law resistance, a resistance box, a one-way key, a two-way key, a jockey, a set square, connecting wires and a piece of sand paper.



Observations:

Range of voltmeter: 5V Least count of voltmeter: 0.05V E.M.F. of battery E: 3V E.M.F. of Laclanche Cell, E₁: 1.45V E.M.F. of Daniel Cell, E₂: 1.125V

Fig. 4.1 : Comparison of e.m.f.'s of two cells

Table for Lengths:						
S. No.	Balancing length when E ₁ (Leclanche Cell) is in the circuit (cm)	Balancing length when E ₂ (Daniel Cell) is in circuit (cm)	Ratio $\frac{E_1}{E_2} = \frac{l_1}{l_2}$			
	(l ₁)	(l ₂)				
1	558	437	558/437 = 1.277			
2	789	617	1.278			
3	848	670	1.266			
4	893	706	1.265			
5	662	521	1.270			

Calculations: Mean $\frac{E_1}{E_2} = 1.271$ (Unit less)

Result: The ratio of E.M.F.'s
$$\frac{E_1}{E_2} \approx 1.27$$

Precautions:

(i) The connections should be neat, clean & tight.

- (ii) The positive poles of the battery E and cells E_1 and E_2 should all be connected to the terminals at the zero of the wires.
- (iii) The jockey should not be rubbed along the wire. It should touch the wire gently.

Sources of Error:

- (i) The auxiliary battery may not be fully charged.
- (ii) The potentiometer wire may not be of uniform cross-section and material density throughout its length.
- (iii) Heating of potentiometer wire by current, may introduce some error.

EXPERIMENT – 5

Aim: To determine the internal resistance of a primary cell using a potentiometer.

Apparatus: A potentiometer, a battery, two one-way keys, a rheostat of law resistance, a galvanometer, a high resistance box, a fractional resistance box (1-10 Ω), an ammeter, a voltmeter (0-5V), a cell, a jockey, a set square, connecting wires & piece of sand paper.



Observations:

- (i) EMF of battery = 2V
 - EMF of cell = 1.35V
- (ii) Table for lengths:

	Position of I	Null pt (cm)	Value of shunt	Internal resistance
Sr. No.	Without shunt R, <i>l</i> 1 cm	With shunt R_1 , $l_2 cm$	resistance $\mathbf{R}(\Omega)$	$\mathbf{r} = \left(\frac{l_1 - l_2}{l_2}\right) R \Omega$
1	571	67	1	7.53
2	619	91	1.5	8.10
3	689	129	2	8.68
4	749	196	2.5	7.05
5	882	221	3	8.97
6	950	289	3.5	7.9

Result: The internal resistance of the given cell is 8.11Ω

Precautions:

- (i) The EMF of the battery should be greater than that of cell.
- (ii) For one set of observations, the ammeter reading should remain constant.
- (iii) Rheostat should be adjusted so that initial will point lies on last wire of potentiometer.

Sources of Error:

- (i) The auxiliary battery may not be fully charged.
- (ii) End resistance may not be zero.
- (iii) Heating of potentiometer wire by current, may introduce some error.

Aim: To determine the resistance of a galvanometer by half-deflection method & to find its figure of merit. Apparatus: A Weston type galvanometer, a voltmeter, a battery, a rheostat, two resistance boxes (10,000 Ω and 500 Ω), two one-way keys, a screw gauge, a meter scale, connecting wires and a piece of sandpaper.



For Half Deflection:

Resistance

 $R(\Omega)$

4500

9500

5200

5700

s.

No.

1

2

3

4

Formulae Used:

(i) The resistant of the given galvanometer as found by half-deflection method:

$$G = \frac{R.S}{R-S}$$

Where R: resistance connected in series with the galvanometer

S: shunt resistance

(ii) Figure of merit:
$$k = \frac{E}{(R+G)\theta}$$

Where E : emf of the cell

 θ : deflection produced with resistance R.

Calculation: Mean G = 70.8 Ω

(i) For G : Calculate G using formula.

Take mean of all values of G recorded in table.

(ii) For k: Calculate k using formula & record in table. Take mean of values of k.

Result:

(i) Resistance of Galvanometer by half – deflection method:

$$G = 70.8 \Omega$$

(ii) Figure of merit, $k = 2.19 \times 10^{-5} \text{ A/div}$

Precautions:

(i) All the plugs in resistance boxes should be tight.

(ii) The emf of cell or battery should be constant.

(iii) Initially a high resistance from the resistance box (R) should be introduced in the circuit. Otherwise for small resistance, an excessive current will flow through the galvanometer or ammeter & damage them.

Sources of error:

- (i) Plug of the resistant boxes may not be clean.
- (ii) The screws of the instruments maybe loose.
- (iii) The emf of the battery may not be constant.



Shunt

resistance

S(Ω)

70

70

70

70

Deflection in

galvanometer

 (θ)

30

14

26

24

For Figure of Merit:

S. No.	Emf of the cells E (v)	Resistance from R. B. R Ω	Deflection $ heta$ (div.)	Figure of Merit K = $\frac{E}{(R+G)\theta}$
1	1.5 x 2 = 3	4500	30	2.18 x 10 ⁻⁵
2	3	9500	14	2.23 x 10 ⁻⁵
3	3	5200	26	2.18 x 10 ⁻⁵
4	3	5700	24	2.16 x 10 ⁻⁵

Half

Deflectio

n

 $\theta/2$

15

7

13

12

Galvanometer

Resistance

71.1

70.5

70.9

70.8

RS

 $\frac{1}{R-S}$

Mean K = 2.19 x 10⁻⁵ A/div.

Aim: To convert the given galvanometer (of known resistance & figure of merit) into an ammeter of desired range & to verify the same.

Apparatus: A Weston type galvanometer whose resistance & figure of merit are given, a constantan or manganin wire, a battery, one-way key, a rheostat, a milli-ammeter, connecting wires, sand paper etc.



Fig. 7(A) - 1 : Converted Galvanometer into an ammeter.

Formulae Used:

To convert a galvanometer which gives full scale deflection for current IG into an ammeter of range O to IO amperes,

the value of required shunt is given by: $S = \left(\frac{I_G}{I_o - I_G}\right)G$

Required shunt resistant S is made using a uniform wire whose, specific resistance is ρ (known) & its length:

$$l = \frac{\pi r^2 S}{\rho}$$

Observations: Given resistance of galvanometer, $G = 70.8 \Omega$

Given value of figure of merit, $k = 2.19 \times 10^{-5} \text{ A div}^{-1}$

Total no. of divisions on either side of zero, $N_0 = 30$

Current for full scale deflection,
$$I_G = N_o \times k = 6.57 \times 10^{-4} \text{ A}$$

Table for Verification:

a) Calculation of value of shunt resistance:

* Required range of converted ammeter,
$$I_0 = 3A$$

* Value of shunt resistance,

$$\mathbf{S} = \left(\frac{I_G}{I_o - I_G}\right) \times G = 0.0155 \,\Omega$$

* Computing the length of the wire to make resistance of 0.155 Ω

b) Observations for diameter of the wire:

(i) Pitch of screw gauge, p = 1 mm

(ii) No. of division of circular scale = 100

(iii) Least count, a = 0.01 mm

(iv) Zero error, e = 0.0 mm

(v) Diameter of the wire = 0.98 mm, Radius = 0.049 cm

c) Specific resistance of material of wire, $\rho = 1.92 \times 10^{-6} \ \Omega cm$

d) Required length of the wire,

$$l = S \times \frac{\pi r^2}{\rho}$$
 = $\frac{0.0155 \times 3.14 \times (0.049)^2}{1.72 \times 10^{-6}}$ cm = 60.8 cm

Verification: Checking the performance of the converted ammeter:

	c	Galvanometer Reading		Ammeter	F	
3A	No.	$\frac{\text{Deflection}}{\theta}$	$\mathbf{Current}$ $\mathbf{I_I} = \theta \times LC$	Reading $I_2 = n \times LC$	$(I_2 - I_1) A$	
	1	3	3 x 0.1 = .3	6 x .05 = 0.3	0.0	
	2	5	0.5	11 x 0.05 = .55	0.05	
	3	7	0.7	15 x 0.05 = .75	0.05	
	4	9	0.9	19 x 0.5 = .95	0.05	

Current indicated by full scale deflection (N_o) of converted ammeter. $I_o = 3A$

Least count of converted ammeter, $\vec{k} = \frac{I_o}{N_o} = 0.1 A/div.$

Result:

- Current I_G for full scale deflection = 6.57 x 10^{-4} A
- Resistance of shunt required to convert the galvanometer into ammeter, S = 0.0155Ω
- Required length of wire, l = 60.8 cm
- As error l' l is very small, conversion is verified.

Precautions & Sources of Error:

- (i) All connections should be neat & tight.
- (ii) The diameter of the wire for making shunt resistance should be measured accurately for diameter is taken in two mutually perpendicular directions.
- (iii) The terminal of the ammeter marked positive should be connected to positive pole of the battery. Also ammeter should be in series with circuit.

PHYSICS TERM - 2 PRACTICAL'S

Aim: To find the focal length of a convex mirror using a convex lens.

Apparatus: An optical bench with four uprights (2 fixed upright in middle two outer uprights with lateral movement), convex lens, convex mirror, a lens holder, a mirror holder, 2 optical needles (one thin, one thick), a knitting needle, a half meter scale.



Fig. : 10.1 Focal Length of Convex Mirror

Formula Used:

Focal length of a convex mirror $f = \frac{R}{2}$

Where R is radius of curvature of the mirror.

Observation:

(i) Actual length of knitting needle, x = 15 cm.

(ii) Observed distance between image needle I and back of convex mirror, y = 15 cm

(iii) Index error = y - x = 15 - 15 = 0 cm No index correction

Observation Table:

	Radius of			
Object needle	Lens	Mirror	Image needle	Curvature
0 (cm)	L cm	M cm	I (cm)	MI (cm)
25	50	56	70.5	14.5
28.5	50	60	73.3	13.3
31.5	50	65	78.4	13.4
30.5	50	60	74	14
)	bject needle 0 (cm) 25 28.5 31.5 30.5	bject needle Lens 0 (cm) L cm 25 50 28.5 50 31.5 50 30.5 50	bject needle Lens Mirror 0 (cm) L cm M cm 25 50 56 28.5 50 60 31.5 50 65 30.5 50 60	bject needleLensMirrorImage needle0 (cm)L cmM cmI (cm)25505670.528.5506073.331.5506578.430.5506074

Mean R = 13.8

Calculation:

Mean corrected MI = R = 13.8 cm

$$f = \frac{R}{2} = 6.9 \ cm$$

Result:

The focal length of the given convex mirror = 6.9 cm

Precautions:

(i) The tip of the needle, centre of the mirror & centre of lens should be at the same height.

(ii) Convex lens should be of large focal length.

(iii) For one set of observations, when the parallax has been removed for convex lens alone, the position of the lens & needle uprights should not be changed.

Aim: To find the focal length of a convex lens by plotting a graph:

(i) between u and v (ii) between $\frac{1}{u}$ and $\frac{1}{v}$

Apparatus: An optical bench with three uprights, a convex lens, lens holder, two optical needles, a knitting needles & a half-metre scale.



Fig. 11.1 : Focal Length of Convex Lens

Formula Used:

The relation between *u*, *v* and *f* for convex lens is:

 $\frac{1}{f} = \frac{1}{v} - \frac{1}{u}$

Where *f*: focal length of convex lens

u: distance of object needle from lens' optical centre.

v: distance of image needle from lens' optical centre.

Observations:

(i) Rough focal length of the lens = 10 cm

(ii) Actual length of knitting needle, x = 15 cm.

(iii) Observed distance between object needle & the lens when knitting needle is placed between them, y = 15.2 cm.

(iv) Observed distance between image needle & the lens when knitting needle is placed between them, z = 14.1 cm.

(v) Index correction for the object distance u, x - y = -0.2 cm

(vi) Index correction for the image distance v, x - z = +0.9 cm

Observation Table:

	Position of: (cm)						
S. No.	Object needle	Lens	Image needle	u (cm)	v (cm)	$1/v (cm^{-1})$	1/u (cm ⁻¹)
1	66	50	26	16	24	0.041	0.062
2	67	50	27	17	23	0.043	0.058
3	68	50	28	18	22	0.045	0.055
4	70	50	30	20	20	0.05	0.05
5	75	50	33	23	17	0.058	0.043
6	80	50	34	24	16	0.062	0.041

Calculation of focal length by graphical method:

(i) u - v graph: The graph is a rectangular hyperbola: Scale: X' axis: 1 cm = 5 cm of uY' axis: 1 cm = 5 cm of vAB = AC = 2f or OC = OB = 2f



 $\therefore f = \frac{OB}{2} \text{ and also } f = \frac{OC}{2}$ $\therefore \text{ Mean value of } f = 10.1 \text{ cm.}$ (ii) $\frac{1}{u} - \frac{1}{v} \operatorname{graph}$: The graph is a straight line. Scale; X' axis: 1 cm = 0.01 cm⁻¹ of $\frac{1}{u}$ Y' axis: 1 cm = 0.01 cm⁻¹ of $\frac{1}{v}$ Focal length, $f = \frac{1}{OP} = \frac{1}{OQ} = 10.2 cm.$ **Result:** (i) From *u*-*v* graph is, f = 10.1 cm

(ii) From $\frac{1}{u} - \frac{1}{v}$ graph is, $f = 10.2 \ cm$



Precautions:

(i) Tips of object & image needles should be at the same height as the centre of the lens.

(ii) Parallax should be removed from tip-to-tip by keeping eye at a distance at least 30 cm. away from the needle.

(iii) The image & the object needles should not be interchanged for different sets of observations.

EXPERIMENT – 10

Aim: To find the focal length of a concave lens using a convex lens.

Apparatus: An optical bench with four uprights, a convex lens (less focal length), a concave lens (more focal length), two lens holder, two optical needles, a knitting needle & a half – metre scale.



Formulae Used: From lens formula, we have:

$$f = \frac{uv}{u - v}$$

Observations:

Actual length of knitting needle, x = 15 cm.

Observed distance between object needle & the lens when knitting needle is placed between them, y = 15 cm. Observed distance between image needle & the lens when knitting needle is placed between them, z = 15 cm. Index correction for u = x - y = 0 cm Index correction for v = x - z = 0 cm

Observation Table:

a N	Position of (cm)						c uv	
S. No.	0 (cm)	L_1 at O_1	Ι	\mathbf{L}_2	ľ	$u = IL_2$	$v = I^{2}L_{2}$	$J = \frac{1}{u - v}$
1	29	50	75	69	78	6.0	9.0	-18.0
2	27	50	71.5	65	77.5	6.5	12.5	-13.54
3	25	50	70.5	65	72.8	5.5	7.8	-18.64
4	28	50	71.3	63	71.2	8.3	8.2	-17.45

Calculations:

 $Mean f = \frac{f_1 + f_2 + f_3 + f_4}{4}$

$$= -16.9$$
 cm ≈ -17 cm.

Result: The focal length of given concave lens = -17 cm.

Precautions:

(i) The lenses must be clean.

(ii) A bright image should be formed by lens combination.

(iii) Focal length of the convex lens should be less than the focal length of the concave lens, so that the combination is convex.

EXPERIMENT – 11

Aim: (i) To determine angle of minimum deviation for a given prism by plotting a graph between angle of incidence & angle of deviation.

(ii) To determine the refractive index of the material (glass) of the prism.

Apparatus: Drawing board, a white sheet of paper, prism, drawing pins, pencil, half metre scale, office pins, graph paper & protector.



Formulae Used:

The refractive index, μ of the material of the prism is given by:

$$\mu = \frac{\sin\left(\frac{A+Dm}{2}\right)}{\sin\left(\frac{A}{2}\right)}$$

Where D_m is the angle of minimum deviation & A is the angle of prism.

Calculations:

From graph between angle of incidence, $\angle i$ and angle of deviation, we get the value of D_m (angle of minimum deviation): $D_m = 37.8^\circ$





Result:

(i) From $\angle i - \angle D$ graph we see that as $\angle i$ increases, $\angle D$ first decreases, attains a minimum value (D_m) & then again starts increasing for further increase in $\angle i$.

(ii) Angle of minimum deviation = $D_m = 37.8^{\circ}$

(iii) Refraction index of material of prism, $\mu = 1.5077$

Precautions:

(i) The angle of incidence should be between $30^{\circ} - 60^{\circ}$.

(ii) The pins should be fixed vertical.

(iii) The distance between the two pins should not be less than 8 cm.

Sources of Error:

(i) Pin pricks may be thick.

(ii) Measurement of angles maybe wrong.

EXPERIMENT – 12

Aim: To determine the refractive index of a glass using travelling microscope. Apparatus: A marker, glass slab, travelling microscope, lycopodium powder.



Formulae Used:

Refractive index
$$\mu = \frac{real \ depth}{apparent \ depth} = \frac{r_3 - r_1}{r_2 - r_1}$$

Observations:

Least count of travelling microscope = 0.001 cm or 0.01 mm

Mean values: $r_1 = 0 \text{ mm}$ $r_2 = 6.81 \text{ mm}$ $r_3 = 10.25 \text{ mm}$

Observations: Reading of Microscope focused on:

S. No.	Mark without slab	Mark with slab on it	Powder on top of slab	
	$r_1 = M + n \times LC \min$	$\mathbf{r}_2 = \mathbf{M} + \mathbf{n} \mathbf{x} \mathbf{L} \mathbf{C} \mathbf{m} \mathbf{i} \mathbf{n}$	$R_3 = M + n \times LC \min$	
1	0	$6.5 + 29 \ge 0.01 = 6.79 \text{mm}$	$10 + 23 \ge 0.01 = 10.23$ mm	
2	0	$6.5 + 31 \ge 0.01 = 6.81 \text{mm}$	$10 + 25 \ge 0.01 = 10.25 \text{mm}$	
3	0	$6.5 + 33 \ge 0.01 = 6.83$ mm	$10 + 27 \ge 0.01 = 10.27$ mm	

Calculations:

Real depth = $d_r = r_3 - r_1 = Mean d_r = 10.25 mm$ Apparent depth = $d_a = r_2 - r_1$ Mean $d_a = 6.81 \text{ mm}$

$$\therefore$$
 Refractive index, $\mu = \frac{real \ depth}{apparent \ depth} = \frac{d_r}{d_a}$ $\therefore \mu = 1.52$

Result:

The refractive index of the glass slab by using travelling microscope is determined as $1.52 = \mu$

Precautions:

(i) Microscope once focused on the cross mark, the focusing should not be disturbed throughout the experiment. Only rack and pinion screw should be turned to move the microscope upward.

(ii) Only a thin layer of powder should be spread on top of slab.

(iii) Eye piece should be so adjusted that cross-wires are distinctly seen.

Aim: To draw the I - V characteristics curve of *p*-*n* junction in forward bias & reverse bias.

Apparatus: A p-n junction semi-conductor diode, a three volt battery, a high resistance, a rheostat, a voltmeter (0-3v), a milli ammeter (0-30 mA), one – way key, connecting wires.



Observations:

Least count of voltmeter = 0.02 & 1 v/div Zero error = -Least count of milli-ammeter = 0.2 mA/div Zero error = -Least count of micro-ammeter = $2 \mu \text{ A/div Zero error} = -$

Observation	Table:
-------------	--------

S. No.	Forward Bias Voltage (V)	Forward Current (mA)	Reverse bias Voltage (V)	Reverse Current (µ A)
1	$10 \ge 0.02 = 0.20$	$2 \ge 0.2 = 0.4$	10 x 1 = 10	5 x 2 = 10
2	0.30	$4 \ge 0.2 = 0.8$	15	16
3	0.40	6 x 0.2 = 1.6	20	22
4	0.50	$11 \ge 0.2 = 2.2$	25	30
5	0.60	$18 \ge 0.2 = 3.6$	30	38
6	0.70	$23 \ge 0.2 = 4.6$	35	48
7	0.80	$31 \ge 0.2 = 6.2$	40	60
8	0.90	$39 \ge 0.2 = 7.8$	45	72





Page 16 (PHYSICS)

Calculations:

Graph is plotted between forward – bias voltage (V_F) (on x-axis) and forward current, I_F (on y – axis) Scale: X – axis: 1 cm = V of V_F Y – axis: 1 cm = mA of I_F Graph is plotted between reverse bias voltage, V_R (along X' axis) and reverse current, I_R (along Y' axis). Scale: X' axis = 1 cm = V of V_R Y' axis = 1 cm = μA of I_F

Result: The obtained curves are the characteristics curves of the semi-conductor diode.

Precautions:

(i) All connections should be neat, clean & tight. (ii) Key should be used in circuit & opened when the circuit is not being used. (iii) Forward bias voltage beyond breakdown should not be applied.

Sources of error: The junction diode supplied maybe faulty.

EXPERIMENT – 14

Aim: To draw the characteristics curves of a zener diode and to determine its reverse breakdown voltage.

Apparatus: One *p*-*n* junction Zener diode, a power supply with potential divider (0-15V), a resistance of Ω , a micro ammeter of range (0-100 μ A), a voltmeter (0-15V), connecting wires.

Theory:

<u>Zener diode</u>: It is a semi conductor diode; in which *n*-type & *p*-type sections are heavily doped i.e. they have more percentage of impurity atoms. It results into low value of reverse breakdown votage (V_{br}).



The reverse breakdown voltage of a zener diode is called

zener voltage (V_z)- The reverse current that results after the breakdown is called zener current (I_z). Circuit Parameters:

 $V_{I} = Input$ (reverse bias) voltage $V_{o} = Output$ voltage $R_{I} = Input$ resistance, $R_{L} = Load$ Resistance Relation: $I_{L} = I_{I} - I_{z}$ $V_{o} = V_{I} - R_{I}I_{I}$ $V_{o} = R_{I}I_{I}$

S. No.	Input Voltage	Input Current		
5.110	$V_r = n \times LC$	$I_r = n \times LC (mA)$		
1	$5 \ge 0.25 = 1.0$	0		
2	$10 \ge 0.25 = 2.5$	0		
3	$15 \ge 0.25 = 3.75$	0		
4	$20 \ge 0.25 = 5$	0		
5	$25 \ge 0.25 = 6.25$	0		
6	$30 \ge 0.25 = 7.5$	0		
7	$35 \ge 0.25 = 8.75$	$13 \ge 0.05 = 0.65$		
8	$40 \ge 0.25 = 10$	1.8		
9	$41 \ge 0.25 = 10.25$	2.25		
10	$43 \ge 0.25 = 10.75$	3		



Initially as V_I increases, I increases a little.

At breakdown, increase of V_I increases I_1 by large amount.

So that $V_o = V_I - R_I I_I = constant$

This constant value of V_0 is called zener voltage (V_z) or reverse breakdown voltage.

Observations: Least count of voltmeter: 0.25 v/div Least count of milli ammeter: 0.05mA/div

Result: From the graph of I_r vs V_r, the reverse breakdown voltage for the zener diode is 10.75V

Precautions: (i) The Zener diode p-n junction should be connected in reverse-bias i.e. p-terminal to –ve and to positive terminal of battery. (ii) Zero error in the instruments should be adjusted in readings.

(iii) Voltmeter & ammeter of appropriate least counts should be used.